



# Phiroze Sethna Private Limited

Plot No. 101 – A, Road No. 16, Wagle Industrial Estate, Thane 400 604. India.  
Telephone (91 22) 2582 2220, 2581 1408, 2582 7204 Fax : (91 22) 2582 0837  
E Mail : [phirol\\_thane@hotmail.com](mailto:phirol_thane@hotmail.com) Website : [www.phirol.com](http://www.phirol.com)

## Phirol®

(Technical Data Sheet)

## Phirol® Thumb Grade Sealer

Grade : TGS

Number : 338

Rev.: 00

Issue Date : Sept. 2003

---

---

### Description :

Phirol Thumb Grade Sealer is a high consistency sealer used for sealing big joints and gaps in automobile. It cures in to a flexible and adherent sealer with excellent air and water sealing properties. It also provides protection and prevent ingress of dust and moisture, thus preventing corrosion.

### Typical properties:

(Should not be considered as specifications)

Colour : Off white  
Curing Schedule : 140°C x 30 mins  
Consistency : 100 to 75 by penetrometer  
Solid content : 98 % min.  
Hardness : 50 - 60 shore A  
Specific Gravity : 1.4 - 1.6

### Application :

It is applied by means of manual moulding and subsequent pressure by hand.

### Storage :

To be stored indoors, away from direct sunlight, heat source and moisture.

### Shelf Life :

Six months under above conditions.

### Packing:

As per customer requirements.

---

### Note :

It should be appreciated that the above information given here is to the best of our knowledge, true and accurate. However, since conditions under which our products are used are beyond our control, recommendations are made without warranty or guarantee.

(An ISO 9001:2008 Certified company)