



Phiroze Sethna Private Limited

Plot No. 101 – A, Road No. 16, Wagle Industrial Estate, Thane 400 604. India.
Telephone (91 22) 2582 2220, 2581 1408, 2582 7204 Fax : (91 22) 2582 0837
E Mail : phirol_thane@hotmail.com Website : www.phirol.com

Phirol®

(Technical Data Sheet)

Phirol® Windshield Sealer

Grade : WSG

Number : 311 Rev.: 00

Issue Date : July. 2010

Description : Phirol Windshield sealer is a single pack non-drying type caulking sealer. It is used in automobile weather strips to prevent water leakage. It remains in non drying condition for long period.

Typical properties:

Colour	: Grey
Viscosity	: As per agreement with customers
Flow at room temp.	: max. 5 mm.
Water tightness	: No leakages
Heat resistance	: Non drying (50 °c for 48 hrs.)
Specific Gravity	: 1.3 to 1.6

(Should not be considered as specifications)

Application : For application drum press type airless pump having compression ratio of 40 : 1 is recommended.

Storage : To be stored indoors, away from direct sunlight, heat source and moisture.
Shelf Life : Six months under above conditions.

Packing: 250 Kg MS Drum / 25 Kg MS Drum

Note: It should be appreciated that the above information given here is to the best of our knowledge, true and accurate. However, since conditions under which our products are used are beyond our control, recommendations are made without warranty or guarantee.

(An ISO 9001: 2008 certified Company)